



implementable signaling devices		
position	device	symbol
A	push button, 4 x 0.34mm <sup>2</sup>	
A	domed push button, 4 x 0.34mm <sup>2</sup>	
A	push button 2-positions, 4 x 0.34mm <sup>2</sup>	
A	key switch, 4 x 0.34mm <sup>2</sup>	
A	pull switch, 4 x 0.34mm <sup>2</sup>	
A	elbow push switch, 4 x 0.34mm <sup>2</sup>	
A	PGS wired UTP Cat5, 8 wires Ø0,5mm	
B	wall socket: 230V. 3 x 2.5mm <sup>2</sup>	
C	photocell incl. cable	
D	motion sensor incl. cable	

other implementable electrical devices	
INPUT:	- intercom
	- fire alarm system
	potential free contact switch
OUTPUT:	- bel switch
	- alarm system
	Imax. = 400mA

Glassmeasurements in mm		
	WIDTH	HEIGHT
DOORWING	1243	2102

Title: W35S_KONE SD_S_LO		Drawing number:	
Order number:	Page no.:	Projectie ISO-128	
Date:	Scale: --		
Drawn by:	Paper size: A3		
		Accustraart 21	
		Postbus 94	
		3903 LX Veenendaal	
		Tel.: 0318 - 532333	
		Fax: 0318 - 532339	
		Revision number:	
		A:	
		B:	
		C:	
		Copyright by KONE	