



shown: Talos RDR-E02-120°-ø3800-NV
laminated glass 8mm, post 156
PH = 2200/TH = 2400
option: floor element

customer:	code:	remark / others:
project:	unit:	
delivery address:	requested delivery day:	

KONE Revolving door 50 (KR50)-120°-NV-ø3800-ø4800 19082104

Revolving door type Talos RDR-C02
System-diam = ø3800 mm (in 200 mm steps), Ø.....
Outside-diam = system-diam. + 120 mm (the indicated order numbers refer to the outside-Ø)
Clear passage height PH = 2200
Total height TH = 2400

- Body**
- 1908 Laminated glass side panels 8 mm (PH max. 2500 mm)
 - 1908 Metal clad side panels
 - Upper ceiling aluminum raw
 - 19081723 (ø3920 - ø4320) or 19081743 (ø4321 - ø4920) Water proofed execution of outside unit top (TH-16), for stainless steel doors all plates in RAL 9006
 - 19081724 (ø3920 - ø4320) or 19081744 (ø4321 - ø4920) Water trough with drain pipe on outside unit top (TH + 50), for stainless steel doors all plates in RAL 9006
 - 19086551 (ø3920 - ø4320) or 19086552 (ø4321 - ø4920) Insulation of the outside top unit with insulating mats 25 mm, each 500 mm top unit
 - 19081725 + 19081726 (ø3920 - ø4320) or 19081745 (ø4321 - ø4920) Increase of passage height (max. 2500 mm), 100 mm x
 - 19081721 + 19081728 (ø 3920 - ø4320) or 19081746 (ø 4321 - ø4920) Increase of unit Top UT, 100 mm x
 - 19081729 (ø3920 - ø4320) Modification of outside diameter (variation from 200 mm grid space)
 - 19081730 (ø 3920 - ø4320) Wall and top connection, width 200 mm, clamping width 24 mm
 - 19081731 Wall and top connection (refer to drawing No. 2003520001A)
 - Polygonal wall connection or connection on sloping facade on request

- Automation**
- Automation T56, door wings on pendulum bearings, glazig toughened glass 6 mm, with showcase available on request
 - Safety strips on door wings bottom
 - Without lock (night slides with lock)
 - With lock Euro-PZ 60 mm by customer Kaba-PZ 63,5 mm by customer
 - 19081201 (ø3920 - ø4320) or 19081202 (ø4321 - ø4920) Emergency function of foldable door wings (control by customer), rotary fittings in stainless steel, no horizontal handles possible
 - 19081733 Control via integrated door terminal (emergency off-module with LED, escape route symbol, key-switch for customer's PHZ)
 - 19086553 (ø3920 - ø4320) 19086554 (ø4321 - ø4920) Transport opening 120° (door wings foldable without emergency function), control by customer or by option OPL 03; no horizontal handles possible
 - 19086555 (ø3920 - ø4320) 19086556 (ø4321 - ø4920) Increase of passage height (for laminated glass 8 mm and metal clad), PHmm
 - Without handles
 - 19081734 Stainless steel bow-type handles, ø32, vertical, appr. 300 mm, satin finish (standard)
 - 19081735 Stainless steel handles, ø32, vertical, appr. 1950 mm, satin finish
 - 19081736 (ø3920 - ø4320) or 19081747 (ø4321 - ø4920) Stainless steel bow-type handles, ø32, horizontal, total width of door wings, satin finish (not with foldable door wings)
 - Special handles on request
 - 19081218 Second bar lock for foldable door wings, locked from inside, locked from outside (if the door is locked, the glazing bead is inside)

- Night slides**
- 19081737 (ø3920 - ø4320) or 19081748 (ø4321 - ø4920) doorwings outside in 8 mm laminated glass, manual, prepared for customer's profile cylinder Euro-PZ 60 mm, Kaba-PZ 65 mm
 - 19081738 (ø3920 - ø4320) or 19081749 (ø4321 - ø4920) Doorwings outside, metal clad, manual, prepared for customer's profile cylinder Euro-PZ 60 mm, Kaba-PZ 65 mm
 - 19081203 (ø3920 - ø4320) or 19081204 (ø4321 - ø4920) Increase of passage height (for laminated glass 8 mm and metal clad), PHmm
 - 19081740 Motor for night slides, several closings with night access (floor element necessary)
 - 19081741 Monitoring of night slides closed
 - 19081742 Monitoring of night slides closed and locked
 - 19081205 (ø3920 - ø4320) or 19081206 (ø4321 - ø4920) Floor guide (for motor driven versions)

- Finish**
- Silver anodized E6/EV1
 - Powder coated acc. to RAL
 - 19086556 Glass- or metal side panels and door wings powder coated in special colours (Tiger, IGP, NCS, RAL-Design, Sikkens, etc.)
 - 19081078 (ø3920 - ø4320) or 19081079 (ø4321 - ø4920) Side panels and door wings anodized in colours
 - Provided by customer
 - 19081080 (ø3920 - ø4320) or 19081081 (ø4321 - ø4920) Night slides in glass or metal coloured anodized Provided by customer
 - 19081750 (ø3920 - ø4320) or 19081766 (ø4321 - ø4920) Side panels and door wings in stainless steel satin finish, grit 320, grinded lengthwise
 - 19081751 (ø3920 - ø4320) or 19081767 (ø4321 - ø4920) Night slides in glass or metal clad in stainless steel satin finish, grit 320, grinded lengthwise
 - 19081752 (ø3920 - ø4320) or 19081768 (ø4321 - ø4920) Glass side panels and door wings in stainless steel mirror finish S8 (metal side panels on request)
 - 19081753 (ø3920 - ø4320) or 19081769 (ø4321 - ø4920) Night slides in glass, in stainless steel mirror finish S8

Further options on request
Execution subject to technical confirmation!

E02 order-number	glass	metal
outside-ø	3920 4120 4320 4520 4720 4920	19081711 19081712 19081713 19081714 19081715 19081716 19081717 19081718 19081719 19081720 19081721 19081722
system-ø	3800 4000 4200 4400 4600 4800	
clear passage width	PW 1730 1830 1930 2030 2130 2230	
escape route width	PW 1730 1830 1930 2030 2130 2230	

Title: KONE Revolving door 50 (KR50) 120°		Project: ISO-128	Drawing number:
Order number:	Page no.: 1		Revision number:
Date: 10-07-2014	Scale:	A	A:
Drawn by:	Paper size: A2		B:
		Accustraal 21	C:
		Postbus 94	Copyright by KONE
		3903 LX Veerendaal	
		Tel.: 0318 - 532333	
		Fax: 0318 - 532339	